


Product datasheet

Specifications



2nd MX opening voltage release.
standard. Masterpact MTZ2/3
drawout. 200/250 VAC 50/60 Hz.
200/250 VDC

LV848514

Price: 5,350.22 ZAR

Main

Range	MasterPact
Device Short Name	second MX
Product Or Component Type	Voltage release
Device Application	Control
Range Compatibility	Masterpact MasterPact MTZ2 circuit-breaker Masterpact MasterPact MTZ3 circuit-breaker
Voltage Release Type	Shunt trip release

Complementary

Control Type	Standard
[Un] Voltage Power Supply	200...250 V AC 50/60 Hz 200...250 V DC
Threshold Tripping Voltage	0.7...1.1 Un on opening
Holding Power Consumption	4.5 W
Circuit Breaker Mounting Mode	Drawout
Maximum Response Time	60 ms on opening for MasterPact MTZ2 60 ms on opening for MasterPact MTZ3

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	3.5 cm
Package 1 Width	6.5 cm
Package 1 Length	8.5 cm
Package 1 Weight	1.168 kg

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

Well-being performance

Mercury Free

Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

China Rohs Regulation [China RoHS declaration](#)
Product out of China RoHS scope. Substance declaration for your information

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [End of Life Information](#)