


# 653190480300

## Power relay 20 - 30 A









This image is for illustrative purposes only and therefore may not represent the exact product code. Colours may vary.

### Technical description:

High Power relay, Faston 250 with flange mount, Number of poles: 1 NO + 1 NC, Contact circuit: 1 NO, 30 A, AgCdO, DC coil, 48 V, operating from 40.8 to 52.8 V, rated power 1.3 W, resistance 1770 Ω, consumption 27.1 mA, holding voltage 28.8 V, must drop-out voltage 4.8 V, ambient temperature from -40 to +75 °C

[BROWSE PRODUCT PAGE](#)

### Technical Features:

<b>Ambient temperature range:</b>	-40...75 °C
<b>Commercial Description:</b>	"Power relay with mounting lugs on the back and Faston 250 connections Versions available: Type 65.31: 20 A 1 NO + 1 NC Type 65.31-4300: 30 A 1 NO"
<b>Contact configuration:</b>	1 NO
<b>Dimensions:</b>	32.2x57.2x36.5 mm
<b>Electrical life:</b>	50000 cycles
<b>Insulation coil/contacts:</b>	4 kV
<b>Nominal voltage DC:</b>	48 V
<b>Operating range DC:</b>	40.8...52.8 V
<b>Rated contact voltage:</b>	250 V AC
<b>Rated current (contacts):</b>	30 A
<b>Rated power DC:</b>	1.3 W
<b>Supply:</b>	DC coil
<b>Certifications and quality approvals (according to type):</b>	     

The information, technical details, data and features contained in this document are subject to change or modification at any time. It is for information purposes only and does not form the basis of a contract.

### Need more information?

[Contact our sales](#) [Find a dealer](#)